

### LISTING OF THE CLAIMS

The following listing of claims replaces all previous listings in this application.

1. **(Previously Presented)** An electrical cable assembly configured to mate with a receptacle that is at least partially defined by a body of an x-ray device, the electrical cable assembly comprising:

a cable having a plurality of conductors;

a fitting to which the cable is attached; and

a terminal attached to the fitting such that when the electrical cable assembly is mated with the receptacle that is at least partially defined by the x-ray device body, a joint cooperatively defined by the terminal and the fitting is substantially disposed within the receptacle, the terminal comprising:

a terminal element substantially comprising a resilient non-electrically conductive material and having first and second ends, the first end being attached to the fitting; and

a plurality of electrical contacts at least indirectly attached to the terminal element proximate the second end, each of the plurality of electrical contacts being in electrical communication with a corresponding conductor of the cable.

2. **(Original)** The electrical cable assembly as recited in claim 1, wherein the terminal element is substantially in the shape of a cone.

3. **(Original)** The electrical cable assembly as recited in claim 1, wherein the resilient non-electrically conductive material of the terminal element substantially comprises a material selected from the group consisting of: rubber; nylon; silicon; and, polytetrafluoroethylene.

4. **(Original)** The electrical cable assembly as recited in claim 1, further comprising a connector configured and arranged to enable removable attachment of the electrical cable assembly to the receptacle.

5. **(Original)** The electrical cable assembly as recited in claim 1, further comprising an additional terminal attached to the cable.

6.     **(Previously Presented)**         An electrical cable assembly, comprising:  
a cable having a plurality of electrical conductors;  
a fitting to which the cable is attached; and  
a terminal attached to the fitting and configured to be received within a receptacle at least partially defined by a body of an x-ray device, the terminal comprising:  
a terminal element substantially comprising a resilient, non-electrically conductive material and having first and second ends, the first end being joined to the fitting so that a joint is cooperatively defined by the terminal and the fitting, and the terminal element defining a substantially annular groove located proximate the joint; and  
a plurality of electrical contacts at least indirectly attached to the terminal element proximate the second end, each of the plurality of electrical contacts being in electrical communication with a corresponding electrical conductor of the cable.
7.     **(Previously Presented)**         The electrical cable assembly as recited in claim 6, wherein a cross-sectional shape of the substantially annular groove comprises a portion of a circle.
8.     **(Canceled)**
9.     **(Original)**         The electrical cable assembly as recited in claim 6, wherein the terminal element is substantially in the shape of a cone.
10.    **(Original)**         The electrical cable assembly as recited in claim 6, wherein the resilient non-electrically conductive material of the terminal element substantially comprises a material selected from the group consisting of: rubber; nylon; silicon; and, polytetrafluoroethylene.
11.    **(Original)**         The electrical cable assembly as recited in claim 6, further comprising a connector configured and arranged to enable removable attachment of the electrical cable assembly to the receptacle.
12.    **(Original)**         The electrical cable assembly as recited in claim 6, further comprising an additional terminal attached to the cable.

13. **(Previously Presented)** An electrical cable assembly configured to mate with a receptacle, the receptacle included with a body of an x-ray device, the electrical cable assembly comprising:

a cable having a plurality of electrical conductors;

a metal fitting to which the cable is attached; and

a terminal attached to the cable, the terminal comprising:

a terminal element substantially comprising a resilient non-electrically conductive material and having first and second ends, the first end being joined to the metal fitting;

a plurality of electrical contacts at least indirectly attached to the terminal element proximate the second end, each of the plurality of electrical contacts being in electrical communication with a corresponding electrical conductor of the cable; and

means for facilitating control of the diametric expansion of the terminal element disposed within the receptacle that is included with the x-ray device body.

14. **(Original)** The electrical cable assembly as recited in claim 13, wherein the means for facilitating control of the diametric expansion of the terminal element substantially prevents the terminal element from expanding beyond the confines of the receptacle when the electrical cable assembly is mated with the receptacle.

15. **(Original)** The electrical cable assembly as recited in claim 13, wherein the means for facilitating control of the diametric expansion of the terminal element substantially precludes arcing between the electrical cable assembly and the receptacle.

16. **(Original)** The electrical cable assembly as recited in claim 13, wherein the means for facilitating control of the diametric expansion of the terminal element contributes to retention of the terminal element in an operational position relative to the receptacle while the electrical cable assembly is mated with the receptacle.

17. **(Canceled)**

18. **(Previously Presented)** The electrical cable assembly as recited in claim 13, wherein the means for facilitating control of the diametric expansion of the terminal element comprises a joint formed at the connection of the terminal element and the metal fitting and configured and arranged to reside substantially within the receptacle when the electrical cable assembly is mated with the receptacle.

19. **(Original)** The electrical cable assembly as recited in claim 13, wherein the terminal element is substantially in the shape of a cone.

20. **(Original)** The electrical cable assembly as recited in claim 13, wherein the resilient non-electrically conductive material of the terminal element substantially comprises a material selected from the group consisting of: rubber; nylon; silicon; and, polytetrafluoroethylene.

21. **(Original)** The electrical cable assembly as recited in claim 13, further comprising a connector configured and arranged to enable removable attachment of the electrical cable assembly to the receptacle.

22. **(Original)** The electrical cable assembly as recited in claim 13, further comprising an additional terminal attached to the cable.

23. **(Original)** The electrical cable assembly as recited in claim 13, wherein the metal fitting comprises an elbow configuration.

24. **(Previously Presented)** A high voltage electrical cable assembly configured to mate with a receptacle, the receptacle included with a body of an x-ray device, the high voltage electrical cable assembly comprising:

a cable having a plurality of electrical conductors;

a fitting to which the cable is attached; and

a terminal attached to the fitting, the terminal comprising:

a terminal element substantially comprising a resilient non-electrically conductive material and being substantially conical in shape, the terminal element having first and second ends, the first end being attached to the fitting;

a plurality of conductive elements substantially disposed within the terminal element, each of the conductive elements being in electrical communication with a corresponding electrical conductor of the cable; and

a plurality of electrical contacts at least indirectly attached to the terminal element proximate the second end, each of the plurality of electrical contacts being in electrical communication with a corresponding conductive element of the terminal element;

means for facilitating control of the diametric expansion of the terminal element;

and

a connector configured to enable removable attachment of the high voltage electrical cable assembly to the receptacle that is included with the x-ray device body.

25. **(Original)** The high voltage electrical cable assembly as recited in claim 24, wherein the means for facilitating control of the diametric expansion of the terminal element substantially prevents the terminal element from expanding beyond the confines of the receptacle when the electrical cable assembly is mated with the receptacle.

26. **(Original)** The high voltage electrical cable assembly as recited in claim 24, wherein the means for facilitating control of the diametric expansion of the terminal element substantially precludes arcing between the electrical cable assembly and the receptacle.

27. **(Original)** The high voltage electrical cable assembly as recited in claim 24, wherein the means for facilitating control of the diametric expansion of the terminal element contributes

to retention of the terminal element in an operational position relative to the receptacle while the electrical cable assembly is mated with the receptacle.

28. **(Canceled)**

29. **(Original)** The high voltage electrical cable assembly as recited in claim 24, wherein the means for facilitating control of the diametric expansion of the terminal element comprises a joint formed at the connection of the terminal element and fitting and being configured and arranged to reside substantially within the receptacle when the electrical cable assembly is mated with the receptacle.

30. **(Original)** The high voltage electrical cable assembly as recited in claim 24, further comprising a connector configured and arranged to enable removable attachment of the electrical cable assembly to the receptacle.

31. **(Original)** The high voltage electrical cable assembly as recited in claim 24, further comprising an additional terminal attached to the cable.

32. – 37. **(Canceled)**